BA150E Electrically Driven
Sewage and Dewatering Pump
Max. 475 m^3/hour, Max. 35 mwc

Pump specifications:

Type	BA150E D285
Max. flow	475 m^3/hour (2090 US gpm)
Max. pressure	35 mwc (115 ft.)
Solids handling	80 mm (3,15")
Impeller type	Semi-open impeller
Priming system	BBA MP50
Electric motor	37 kW | 4 pole | 400/690V
Motor control	Frequency drive
Display	HMI touchscreen
Canopy	L10-23
Connections	DN150 (6")
Dry weight	Approx. 1650 kg

FEATURES

BA auto prime pump
The BA range of pumps has been designed with a clear focus on reliability, efficiency and durability. Featuring the 100% mechanical priming system, the BA series pumps quickly prime and re-prime, even from dry conditions. The heavy build style of both pump and canopy make the BA range perfect for use in the strenuous contractor market.

World-class performance
The BA range is built to be deployed on the most demanding dewatering and sewage bypassing applications. Using high efficiency pumps and electric motors, the pumps offer maximum performance at minimal cost, fully in-sync with the company philosophy of “Lowest cost of ownership”.

Electric pumps in canopy
- Extremely low noise level
- Maximum safety while running
- Better resistant to vandalism
- More space for your branding
- Optimal weather protection
- Minimal ageing, therefore stable in value

Complete package designed & built by BBA Pumps
- Complete in-house design & production
- Over 70 years of experience in the market
- Extensive testing facility in-house
- Contemporary & functional design
- Durable & eco-friendly materials
- Custom builds available

After sales service & product support
- Single supplier for parts, spares & accessories
- Dedicated customer help-desk (24h service)
- Dedicated service department in-house
- Global parts distribution network
- Optional global on-site servicing
- Extensive training options available (technical & commercial), on-site or in-house

Stackable frame BF10-23 is optional

PERFORMANCE CURVES (1750 RPM)

Continuous duty according to ISO 9906.









STANDARD TECHNICAL SPECIFICATIONS



BBA Pumps auto prime pump

Pump type	BA150E D285
Max. flow	475 m³/hour (2090 US gpm)
Max. head	35 mwc (115 feet)
Impeller type	Semi-open impeller
Solids handling	80 mm (3.15 inch)
Pump casing	Cast iron GG25
Impeller	Chrome Moly 42CrMo4
Self-cleaning wear plate	Chrome Moly 42CrMo4 (cutter slots)
Pump shaft	42CrMo4 heat treated
Shaft seal	Mechanical seal
Seal faces	Tung/Sic
Seal rubbers	Viton

BBA Pumps priming system

Pump type	MP50 diaphragm pump
Air handling capacity	50 m³/h (30 cfm)
Max. vacuum	8,5 m (25 inHg)
Drive	Electric motor 2,2 kW - 400V
Start/stop	Fully automatic
Float box	Aluminium
Non return valve	Cast iron GG25
Check valve disc	Buna-N

Electric motor

Motor brand	Hoyer
Motor type	HMC3 225S-4
Power kW	37 kW (50 Hp)
Rated Voltage	400/690V 50Hz
Current (I nom.)	66 Amp
4-pole	1480 RPM
Efficiency	93,9 %
Protection class	IP55
Thermal protection	PTC
Standard	IEC 60034

BBA Pumps control panel

Touchscreen	HMI Human-Machine Interface
Frequency drive	For variable speed and energy saving
Automatic level control	Start/stop with two float switches
PID control	Level sensor is optional
Languages	Dutch | German | English
Configuration portal	For managing specific functions for users
Actual information	Hour counter, malfunctions, required kWh

All electrical components **safe** and **dry** behind a lockable door.

PUMPS FROM HOLLAND

Semi-open impeller
Corrosion and abrasion resistant Chrome Moly (42CrMo4) semi-open impeller.

Large inspection covers
Easy access to float box, impeller and non-return valve.

Easy inspection
Oil glasses, drain valves and fill plugs are all easily accessible.

Priming system
Diaphragm pump, air-cooled, water-resistant and oil-spillage free.
Air capacity of 50 m^3/hour.

Level sensor is optional
The level sensor, in combination with the built-in PID control, ensures accurate level control and reduces energy consumption.

4-year limited warranty
The BBA Pumps limited warranty covers years or operating hours whichever occurs first.
For more details, please consult the BBA warranty book.

Pictures used are for illustration purposes only.

PUMPS FROM HOLLAND